

应用场所 Application

- 广泛应用于海洋工程各类作业平台、各类化学品、天然气运输船、危险品码头等危险区域作照明之用；
- 可在潮湿、振动、腐蚀等恶劣环境中可靠工作；
- 适用于爆炸性危险环境1区、2区等场所。
- Widely used for the illumination on various marine platforms, chemical tankers, LNG ships and hazardous cargo wharfs, etc..
- Can reliably work in severe environment exposed in moisture, vibration or corrosion;
- Explosive hazardous atmosphere Zone 1, Zone 2.



灯体 Housing

- 不锈钢，表面喷塑
- Stainless steel, powder coated surface

透明罩 Transparent cover

- 钢化玻璃
- Toughened glass

保护网 Protection net

- 不锈钢，表面喷塑
- Stainless steel, powder coated surface

选配表 Selection table

型号 Type	额定电压(V) Rated voltage	额定功率(W) Rated power	光源类型 Lamp source	防爆标志 Ex-Mark	重量(kg) Weight
dF1-25	220V/230V AC 50/60Hz	25W	白炽灯 Incandescent lamp	Ex d IIC T4 Gb	8.9
dF1-60		60W			
dF1-100		100W			
dF1-J9		9W	节能灯 Energy saving lamp	Ex d IIC T6 Gb	
dF1-J11		11W			
dF1-LED 3		3W	LED		
dF1-LED 5		5W			

- 灯具出厂时不配电缆夹紧密接头，由用户自配，如有要求，请注明。
- 灯具出厂时不配光源，若用户需要，请注明。
- The light fitting is supplied without cable gland and could be supplied on request.
- On delivery light fitting is not equipped with light source. Please specify if needed.

技术参数 Technical parameters

执行标准 Conformity to standards	IEC60079, EN60079, GB3836, CCS入级规范 (CCS standard)
环境温度 Ambient temperature	-25°C~+50°C
灯座 Lamp holder	E27
防护等级 Degree of protection	IP56
防腐等级 Corrosion-proof	WF2
电缆引入口 Cable entris	2 × G3/4"压紧螺, 推荐配DQM-II/III G3/4"格兰(黄铜镀镍), 适用于Φ12.5~Φ20.5mm电缆 2×G3/4" gland nut, DQM-II/III G3/4" gland (Nickel plated brass) is recommended, suitable for Φ12.5-Φ20.5mm cable
接线端子 Terminal	3 × 1.5~2.5mm ²

外形尺寸 Outline dimension

