

PARAMETER

GPS Antenna

Size 85mm(L)*24mm(W)*14mm(H)
Working Temperature -25°C to 75°C
Working Voltage 9-90V

Weight 28g
Built-in Battery 55mAh

HARDWARE SPECIFICATION

Location Accuracy	≤5m	Channel	20 Class
GPS Chip	MTK	GPS Sensitivity	-144dBm
GSM Frequency	850/900/1800/1900MHZ	Tracking Sensitivity	-160dBm
Positioning Time	Hot Start<5SEC(Open Sky)	Communication Type	TCP/IP
	Warm Start<30SEC	GPS LED Indicator	Yellow
	Cold Start<40SEC(Open Sky)	GSM LED Indicator	Red
GSM Antenna	Onboard Antenna		

Built-in 18mm*18mm*2mm Ceramic Antenna

Class12. TCP/IP Built-in GSM Module

SOFTWARE SPECIFICATION

OTA Upgrade	Support	Geo-fence	Support
Parameter Setting	SMS Command, Platform	Cut-wire Alarm	Support
GPRS Upload	Upload Interval Every 10 Seconds	Vibration Alarm	Support
Third-party Checking	WEB/APP	Movement Alarm	Support
ACC Detection	0		

FUNCTION



Real-time Tracking



Remotely Cut-off Petrol/Electricity



Vibration Alarm



Disassemble Alarm Detection



Built-in Battery



Rapid Acceleration/Deceleration Alarm

APPLICATION



Car Rental



Auto Insurance



Logistics Transportation