

JVS-N517-SDL

5.0MP Full-Color Video & Audio PoE Network Camera






Features

- Light indicator for network status
- Spotlight on motion detection
- Full-Color with Dual Smart Illumination
- Support Humanoid Detection
- Built-in Mic and Speaker
- With built-in PoE
- Equipped With unique VQC (Video Quality Catalyst) Technology
- Support SD Card

Dimension







Specifications

Specifications	
Video	
Image Sensor	1/3" CMOS Sensor
Max Resolution	2560x1792
Effective Pixels	5.0MP
Compression Standard	H.264/H.265
Framerate	25fps
	Main Stream: 317Kbps ~ 8Mbps
Bitrate	Sub Stream: 68Kbps~2728Kbps
SNR (dB)	52dB
Min. Illumination	0Lux (light ON)
Lens	
Interface Type	M12
Lens	3.6mm, 6mm
	3.6mm:H 80°, V 41.1°, D 94.6°
FOV	6mm:H 49.7°, V 26.6°, D 57.3°
Function	
Audio Codec	G.711U/G.711A (default)
Exposure Control	Auto
White Balance	Auto
Gain Control	Auto
Digital 3D Noise Reduction	Support
OSD Information Setting	Large font OSD, OSD flashing on alarm, OSD position settings
SNTP	Support
Schedule Reboot	Support
Smart Defog	Support
	- ' '
Motion Detection	Support Humanoid Detection
Image Setting	Support Saturation, Brightness, Contrast, Sharpness adjustment
Image Style	Standard, Soft, Transparent
Day and Night Function	Auto, Always Black & White, Always Color, Scheduled Color
Privacy Mask	Support up 8 areas
Night Vision Optimization	Support
DWDR	Support
Screen Settings	Screen mirroring, Screen flipping
IP Adaptation	Support automatic adaptation of IP address (Optional)
Intelligent Analysis	Support Region Intrusion Detection, Line Crossing Detection, Video Blocking Detection,
Alarm Method	People Counting
Alarm Method	Email Alarm, Client Alarm System, Audio and Video, Image, Alarm, Network management, Storage management,
Remote Operation	System, Audio and video, image, Alarm, Network management, Storage management, Intelligent Analysis
Audio Function	Built-in Mic and Speaker
SD Card	Support
VQC Technology	Support
Network	Опрот
Ethernet	10/100Mbps Ethernet
Stream	2x Streams
Network Protocols	HTTP, TCP/IP, UDP, ICMP, RTSP, RTP, RTCP, SMTP, DHCP, DNS
ONVIF	Standard ONVIF
Network Transmission	CloudSEE 2.0
	IE8+, Chrome18+, Firefox5.0+, Safari5.02+
Browser	·
User	Up to 13 Users
App	Support iOS/Android
General	A White LEDe + A ID LEDe
Lights	4 White LEDs + 4 IR LEDs
IR Distance	Up to 50 Meters
Waterproof Level	IP67
Power Supply	DC12V or PoE (IEEE802.3af)
Power Consumption	<3W (During Day); <6W (At Night)
Working Temperature	-20°C ~ 60°C
Working Humidity	10% ~ 90% Rh
Color/Material	Black and White/Plastic
Dimensions (WxHxD)	95x95x175mm
Weight	290g
Installation Method	Wall or ceiling mount (Bracket Optional)