

JVS-N59-Z40

5MP Full-Color PTZ IP Camera



Features

- 5MP Ultra-clear Image Quality Starlight level ultra-low light zoom camera with built-in GPU chip.
- Built in 250m infrared light for supplementary illumination
- Perimeter Prevention: Region Intrusion, Line Crossing, Motion Detection.
- Support Humanoid Tracking Zoom Function.
- External Interface: External Audio Input, External Audio Output, Support Two-way Intercom.
- Support SD card (512G).
- Support timestamps, with absolute millisecond level timestamps for each frame of stream output; 360 ° continuous rotation in the horizontal direction, automatic flipping of 180 ° in the vertical direction from -15 ° to 90 ° , and continuous monitoring without any blind spots.
- Supports 1024 preset positions, 8 cruising paths, 5 tracking

Specifications

Video	
Image Sensor	1/1.8" CMOS Sensor
Max Resolution	2496x1792
Effective Pixels	5.0MP

Compression Standard	H.264/H.265(Default)
Frame Rate	25fps
Bitrate	Main Stream: 256Kbps ~ 8192Kbps Sub Stream: 68Kbps~1024Kbps
SNR (dB)	50dB
Min. Illumination	0Lux (light ON)
Lens	
Interface Type	Non-standard Interface
Lens	40x Optical
Focal length	5.3mm-215mm
Function	
Audio Codec	G.711U/G.711A (Default)
Exposure Control	Auto
White Balance	Auto
Gain Control	Auto
Digital 3D Noise Reduction	Support
OSD Information Setting	Large Font OSD, OSD Flashing on Alarm, OSD Position Settings
SNTP	Support
Schedule Reboot	Support
Smart Defog	Support
Motion Detection	Support Humanoid Detection
Image Setting	Support Saturation, Brightness, Contrast, Sharpness Adjustment
Image Style	Standard, Soft, Transparent
Day and Night Function	Automatic Switching, Timing Switching, Day Mode, Night Mode
Privacy Mask	Support Up To 24 Masking Areas
Night Vision Optimization	Support
DWDR	Support
Screen Settings	Screen Mirroring, Screen Flipping
IP Adaptation	Support Automatic Adaptation of IP Address
Intelligent Analysis	Support Region Intrusion, Line Crossing, Video Tampering Detection
Alarm Method	Email Alarm, Client Alarm
Remote Operation	System, Audio and Video, Image, Alarm, Network management, Storage management, Intelligent Analysis
External Interface	External Audio Input, External Audio Output
SD Card	Support (512G)
Pan/Tilt Range	Pan: 0°~360°; Tilt: -15°~90°
Pan Speed	0°~180°/S
Tilt Speed	0°~75°/S
Network	
Ethernet	10/100Mbps Ethernet
Stream	2x Streams
Network Protocols	HTTP; HTTPS; IPv4; RTSP; UDP; SMTP; NTP; DHCP; DNS; DDN; 802.1x; Qos; FTP; UPnP; ICMP; SNMP; IGMP; RTP; PPPoE; RTMP; TCP
ONVIF	Standard ONVIF
Network Transmission	CloudSEE 3.0, Onvif
Browser	IE8+, Chrome18+, Firefox5.0+, Safari5.02+
User	Up to 13 Users
App	Support iOS/Android
General	
Lights	13 infrared and laser lights
Fill Light Distance	Warm Light: 60 Meters IR LED:250 Meters
Network interface	RJ45*1 SFP*1

Alarm interface	Alarm in*2 Alarm Out*2
Waterproof Level	IP67
Power Supply	DC12V/3.33A or PoE
Power Consumption	≤25W
Working Temperature	-20°C ~ 60°C
Working Humidity	0% ~ 93% Rh
Color/Material	Front Ball Shell: Aluminum Alloy Black; Rear Ball Shell: ABS Black; Bracket: Aluminum Alloy White
Dimensions (WxHxD)	400x325x325mm
Weight	3500g
Installation Method	Wall Mount