

# JVS-N915-XDL

## 3.0MP Dual Light Video & Audio PoE Network Camera



### Features

- Dual Smart Illumination
- Support Motion Detection(Humanoid)
- Built-in Mic
- Built-in PoE
- IP67

### Specifications

| Video                      |                                                                    |
|----------------------------|--------------------------------------------------------------------|
| Image Sensor               | 1/2.7" CMOS Sensor                                                 |
| Max Resolution             | 2304x1296                                                          |
| Effective Pixels           | 3.0MP                                                              |
| Compression Standard       | H.264/H.265/H265+                                                  |
| Framerate                  | 20fps                                                              |
| Bitrate                    | Main Stream: 256Kbps ~ 4Mbps<br>Sub Stream: 68Kbps~1024Kbps        |
| SNR (dB)                   | 39dB                                                               |
| Min. Illumination          | 0Lux (light ON)                                                    |
| Lens                       |                                                                    |
| Interface Type             | M12                                                                |
| Lens                       | 2.8mm, 3.6mm                                                       |
| FOV                        | 2.8mm:H 96° , V 53° , D 110°<br>3.6mm:H 83.8° , V 42.7° , D 100.1° |
| Function                   |                                                                    |
| Audio Codec                | G.711U/G.711A (default)                                            |
| Exposure Control           | Auto                                                               |
| White Balance              | Auto                                                               |
| Gain Control               | Auto                                                               |
| Digital 3D Noise Reduction | Support                                                            |
| OSD Information Setting    | Large font OSD, OSD flashing on alarm, OSD position settings       |
| SNTP                       | Support                                                            |
| Schedule Reboot            | Support                                                            |
| Smart Defog                | Support                                                            |
| Motion Detection           | Support(Humanoid)                                                  |

|                                  |                                                                |
|----------------------------------|----------------------------------------------------------------|
| <b>Image Setting</b>             | Support Saturation, Brightness, Contrast, Sharpness adjustment |
| <b>Image Style</b>               | Standard, Soft, Transparent                                    |
| <b>Day and Night Function</b>    | Auto, Always Black & White, Always Color, Scheduled Color      |
| <b>Privacy Mask</b>              | Support up to 8 areas                                          |
| <b>Electronic Screen Setting</b> | Support maximum and minimum exposure time setting              |
| <b>Night Vision Optimization</b> | Support                                                        |
| <b>DWDR</b>                      | Support                                                        |
| <b>Screen Settings</b>           | Screen mirroring, Screen flipping                              |
| <b>IP Adaptation</b>             | Support automatic adaptation of IP address (Optional)          |
| <b>Alarm Method</b>              | Email Alarm, Client Alarm                                      |
| <b>Remote Operation</b>          | System, Audio and Video, Image, Alarm, Network management      |
| <b>Audio Function</b>            | Built-in Mic                                                   |
| <b>Network</b>                   |                                                                |
| <b>Ethernet</b>                  | 10/100Mbps Ethernet                                            |
| <b>Stream</b>                    | 2x Streams                                                     |
| <b>Network Protocols</b>         | HTTP, TCP/IP, UDP, ICMP, RTSP, RTP, RTCP, SMTP, DHCP, DNS      |
| <b>ONVIF</b>                     | Standard ONVIF                                                 |
| <b>Network Transmission</b>      | CloudSEE 2.0                                                   |
| <b>Browser</b>                   | IE8+, Chrome18+, Firefox5.0+, Safari5.02+                      |
| <b>User</b>                      | Up to 13 Users                                                 |
| <b>App</b>                       | Support iOS/Android                                            |
| <b>General</b>                   |                                                                |
| <b>Lights</b>                    | 4 White LEDs + 4 IR LEDs                                       |
| <b>IR Distance</b>               | Up to 40 Meters                                                |
| <b>Waterproof Level</b>          | IP67                                                           |
| <b>Power Supply</b>              | DC12V or PoE (IEEE802.3af)                                     |
| <b>Power Consumption</b>         | <3W (During Day); <6W (At Night)                               |
| <b>Working Temperature</b>       | -30℃~60℃ (-22℉~140℉)                                           |
| <b>Working Humidity</b>          | 10% ~ 90% Rh                                                   |
| <b>Color/Material</b>            | Black and White/Plastic+Metal                                  |
| <b>Dimensions (WxHxD)</b>        | 67x74x201mm                                                    |
| <b>Weight</b>                    | 250g                                                           |
| <b>Installation Method</b>       | Wall or ceiling mount                                          |