

JVS-N519-PWL

5MP Full Color PoE IP Camera (ColorNext Pro Series)

Specifications

CAMERA	
Image Sensor	1/1.79" Progressive CMOS
Min. Illumination	IR ON 0 Lux
Day & Night	IR cut filter with auto switch
Lens	3.6mm
FOV	H: 88.9°; V: 47.3°; D:103.7°
LEDs	18 Pcs Warm LED
LED Range	Up to 65m
LED Adjustment	Adaptive Dimming
IMAGE	
Max Resolution	2560x1792
Frame Rate	25fps
Video Compression	H.265/H.264
Bit Rate (CBR/VBR)	Main Stream: 256 ~ 8192Kbps Sub Stream: 68 ~ 1024Kbps
Audio Compression	G.711a / G.711u
Image Setting	Saturation, Brightness, Contrast, Sharpness
Image Enhancement	BLC/HLC/3D DNR/Defog
White Balance	Auto
Privacy Mask	Support 8 Rectangle Areas
DWDR	Support
NETWORK	
Network Protocols	HTTP, TCP/IP, UDP/IP, ICMP, RTP, UDP, RTCP, S
Interface Protocols	Standard ONVIF, GB28181, CloudSEE
Auto IP Configuration	Support
Alarm Trigger	Motion Detection, Region Intrusion, Line Crossing
RTSP Video	Standard RFC2326, QuickTime/VLC Player etc.
Security	User security authentication, Reset, Hardware Wa
Web Language	Chinese, English
Browser	IE8+, Chrome18+, Firefox5.0+, Safari5.02+
INTERFACE	
Ethernet	1 RJ45 10M / 100M Ethernet
Audio	Built-in Mic and Speaker
SD Card	Not Support
Reset Button	Not Support
GENERAL	
Power Supply	DC12V/2A, PoE IEEE 802.3af
Power Consumption	<3W (During day); <13W (At night)
Working Temperature	-30℃~60℃(-22°F~140°F)
Working Humidity	10% ~ 90% Rh Non-Condensation
Dimensions	262x112x155(mm)
Product Weight	≤700g
Color / Material	Front Shell: Black ADC12; Rear Shell: White PC
Installation	Wall, Ceiling



Features

- 5.0 Megapixel 2560x1792 Resolution.
- Full Color Night Vision
- Equipped with VQC Technology
- F1.0 Aperture
- 18x LEDs and Support Adaptive Dimming
- Built-in Mic and Speaker
- IEEE802.3af PoE
- Ingress Protection IP67

Dimension(mm)

