

JVS-H320C

3MP Wi-Fi Pan/Tilt Camera



Features

- 3MP Ultra-clear Image Quality;
- Built-in Speaker + MIC;
- Support Wi-Fi Connection, Wired Connection and AP Connection;
- Support Humanoid Detection;
- Support SD Card, Maximum Support 256G;
- Support Region Intrusion, Line Crossing, Video Tampering Detection;

Specifications

Video	
Image Sensor	1/2.9" CMOS Sensor
Max Resolution	2304x1296
Effective Pixels	3.0MP
Compression Standard	H.264/H.265(Default)
Frame Rate	25fps
Bitrate	Main Stream: 128Kbps ~ 4096Kbps Sub Stream: 68Kbps~1024Kbps
SNR (dB)	50dB
Min. Illumination	0.01Lux (light ON)
Lens	

Interface Type	M12
Lens	3.6mm
FOV	H: 78.6°, V: 42°, D: 92.4°
Function	
Audio Codec	G.711U/G.711A (Default)
Exposure Control	Auto
White Balance	Auto
Gain Control	Auto
Digital 3D Noise Reduction	Support
OSD Information Setting	Large Font OSD, OSD Flashing on Alarm, OSD Position Settings
SNTP	Support
Schedule Reboot	Support
Smart Defog	Support
Motion Detection	Support Humanoid Detection
Image Setting	Support Saturation, Brightness, Contrast, Sharpness Adjustment
Image Style	Standard, Soft, Transparent
Day and Night Function	Automatic Switching, Timing Switching, Day Mode, Night Mode
Privacy Mask	Support Up To 8 Masking Areas
Night Vision Optimization	Support
DWDR	Support
Screen Settings	Screen Mirroring, Screen Flipping
IP Adaptation	Support Automatic Adaptation of IP Address
Intelligent Analysis	Support Region Intrusion, Line Crossing, Video Tampering Detection, Defocus Detection
Alarm Method	Email Alarm, Client Alarm
Remote Operation	System, Audio and Video, Image, Alarm, Network management, Storage management, Intelligent Analysis
Audio Function	Built-in Mic and Speaker
Storage	Support SD Card (256G) ,Cloud Storage
Reset Button	Support
Network	
Ethernet	10/100Mbps Ethernet
Stream	2x Streams
Network Protocols	HTTP, TCP/IP, UDP, ICMP, RTSP, RTP, RTCP, SMTP, DHCP, DNS
ONVIF	Standard ONVIF
Network Transmission	CloudSEE 2.0
Browser	IE8+, Chrome18+, Firefox5.0+, Safari5.02+
User	Up to 13 Users
App	Support iOS/Android
General	
Lights	2 White LEDs + 6 IR LEDs
Fill Light Distance	IR LED:40 Meters
Waterproof Level	IP66
Power Supply	DC12V/2A
Power Consumption	<6W (During Day); <10W (At Night)
Working Temperature	-30℃~60℃(-22℉~140℉)
Working Humidity	10% ~ 90% Rh
Color/Material	Black and white /PC+ABS
Dimensions (WxHxD)	135x135x95mm
Weight	450g
Installation Method	Wall Mounting, Lifting and Pole Mounting